





THE PURPOSE

This document is composed to assist our clients and the supply chain with a high-level understanding of the benefits and services associated with Robotics used for Non-Intrusive Inspection.




































2 DATA SHEET - ROBOTICS FOR NON-INTRUSIVE INSPECTION (NII) www.sonomatic.com 3

ROBOTICS FOR NII

Sonomatic are working with the UK Oil and Gas Technology Centre (OGTC) to design and build a semiautonomous inspection robot. The robot can be used for corrosion mapping inspection projects, for example, a Non-Intrusive Inspections (NII) campaign, however it can be used on other inspection projects. The robot will provide rapid inspection with full real world positional tracking and autonomy, freeing up the inspection technician to carryout inspections on other areas.

THE ISSUE

There is a growing interest in using NII for inspections across industry sectors. NII offers the following

- Moreover Inspections can be done with equipment on-line.
- Production is not affected by inspection requirements (reduced TAR (turn around and shutdown) durations).
- Avoids the need for personnel entry.
- **Ost of inspection is lower.**
- MII provides quantitative data on equipment condition more efficient and effective integrity

There are three main types of NII inspection:

- Type A, where the aim is to confirm absence of corrosion through sampling inspection.
- Type B, where the aim is to sample sufficient areas of the vessel to allow robust statistical analysis to estimate the condition of the uninspected regions.
- Type C, where high (100%) coverage of the vessel is required because sampling is not justifiable. This typically applies when expected degradation is severe or inhomogeneous, i.e. it is not possible to predict the location of degradation.

The costs of gathering the required information through limited coverage (supported by statistical analysis) for Type A and B are lower than is required for Type C. Scanners tend to be relatively slow and heavy and require high levels of technician input. There is a need for a faster, semi-autonomous scanner to facilitate faster, more efficient NII.







FEATURES


This project objectives are to deliver a highly manoeuvrable lightweight scanner which will allow rapif inspection of areas autonomously.

Hardware

A small, battery powered lightweight scanner with air coupled (or similar) inspection system to remove need for an irrigated couplant feed. Highly manoeuvrable to allow rapid travel on surfaces with obstructions.

Software

Built in positional and automated navigation system to allow minimal operator intervention. Integration with 3D modelling software to allow automated generation of 3D maps and rapid processing of inspection data and report generation.



Time of Flight Diffraction inspection for wall loss at weld roots (100% coverage) Time of Flight Diffraction inspection for wall loss at weld roots (Sampling)

- Nominal thickness: 10.0 mm (shell) / 10.0 mm (ends)
- Operating temperature ≈ 38 °C
- Material: Carbon Steel


Nozzle ID	Size (DN)	Size (inch)	SCH	Nom T (mm)	Description
N1	100	4	80	8.56	Inlet
N2	100	4	80	8.56	outlet
N3	50	2	160	8.74	recycle
N4	100	4	80	8.56	spare
N5	100	4	80	8.56	vent
N6	100	4	80	8.56	spare
N7	50	2	160	8.74	pressure conn
N8	100	4	80	8.56	rupture disc
N9	50	2	160	8.74	temp conn
N10	150	6	STD	7.11	level element
N11	50	2	160	8.74	drain
M1	500	20	XS	12.7	manway

BENEFITS

- Marrove positional accuracy and inspection repeatability.
- Market Ma
- Reduce reporting times and improving reporting accuracy.
- Improve accuracy of statistical analysis and trending.
- Reduce man hours onsite.

OA AND HS&E

Sonomatic operate under an integrated QHSE management system and are committed to the highest quality and safety of service provision | ISO 9001: 2015: 00007140 | ISO 14001:2015: 00037371 | ISO 45001:2018:00037372 | ISO 17020: 2012: 4276 | Achilles FPAL Verified: 076712 | SEQual 1988 | British Safety Council Member: S0388440







CONTACTS

EUROPE AND AFRICA

Robert Cumming

Integrity Manager & Software Team Lead

T: +44 (0)1224 823960

E: Robert.Cumming@sonomatic.com

Graham Marshall

Subsea Project Manager

T: +44(0)1224823960

E: Graham.Marshall@sonomatic.com

Stuart Ley

Topside Project Manager

T: +44(0)1224823960

E: Stuart.Ley@sonomatic.com

Danielle Gunns

Project Delivery Manager (Warrington)

T: +44(0) 1925 414 000

E: Danielle.Gunns@sonomatic.com

AUSTRALASIA

Jonathan Millen

Australia West Coast Project Manager

T: +61 415 850 346

E: Jon.Millen@sonomatic.com.au

Judd McCann

Australia East Coast Project Manager

T: +61 488 442 019

E: Judd.McCann@sonomatic.com.au

Zach McCann

South East Asia Regional Manager

T: +61 404 797 670

E: Zach.McCann@sonomatic.com.my

Alex Cesan

Australia & South East Asia General Manager

T: +61 498 442 666

E: Alex.Cesan@sonomatic.com.au

AMERICAS

Esteban Cesan

General Manager Americas

T: +1832 977 0303

E: Esteban.Cesan@sonomatic.com

MIDDLE EAST

Gordon Reid

Regional Manager

T: +971 26 580 708

E: Gordon.Reid@sonomatic.com



